

3-OUNCE FOAM-FLUSH NEPON TOILET



Clivus New England, Inc.
PO Box 127 • North Andover, MA 01845
Tel: 978-794-9400 • Fax: 978-794-9444
E-mail: 123CNE@clivusne.com • www.clivusne.com

- **Saves water:**
Thanks to the foaming action of the Neponol Soap, the Nepon Toilet can be flushed using only 3-ounces of water.
- **No splashing:**
Foam “blanket” prevents splashing.
- **Hygienic:**
Neponol foam-flush action prevents “streaking” and keeps the toilet bowl clean at all times.
- **Programmable control:**
Microcomputer with adjustable settings initiates intermittent foaming cycle; push-button initiates foam-flush.
- **Neponol:**
An alcohol-type, biodegradable soap displaying superior cleaning, foaming, and lubricating effects. One bottle of Neponol lasts an average of one month.



Specifications

Model:	3-ounce foam-flush
Weight:	88 pounds including packaging
Power:	120V AC
Power Consumption:	Normal – Approx. 4 watts; Foam flush – Approx. 8 watts for 45 seconds
Toilet body material:	Vitreous ceramic
Water tank material:	Vitreous ceramic
Water tank capacity:	9.5 quarts
Toilet seat material:	ABS U-shaped
Toilet lid material:	ABS
Center line to finished back wall:	22” with 4” PVC waste line <u>only</u>
Finished side wall to center:	15” minimum
Minimum toilet plumbing pipe angle:	45 degrees from horizontal or steeper
Air pump:	Diaphragm electro magnetic system
Flush duration:	Normal: 45 seconds (or variable from 30 to 60 seconds)
Foaming elements:	Polystyrene fabric
Water supply required:	Yes; provide on either side of toilet
Water supply control:	Automatic float
Neponol soap:	An alcohol-type, biodegradable, mild soap
Color:	Ivory
ADA compliant:	Yes
Warranty:	One year